



PRODUCT: Various Philips VARI*LITE Luminaires

SUBJECT: Front Lens Accessory Mounting Screw Hole Size Information

OVERVIEW

This technical notice is for informational purposes only. Users and owners are not required to inspect their Philips VARI*LITE luminaires. This notice should be kept for future reference.



Note: Service and routine maintenance to Philips VARI*LITE luminaires should be done by an Authorized Service Center or trained and qualified personnel only.

FRONT LENS ACCESSORY SCREW HOLE SIZES


The following Philips VARI*LITE luminaires have screw holes on the front of the luminaire head assembly to mount accessories. Refer to [Table 1, “Front Mounted Accessory Screw Hole Sizes,”](#) for screw size/thread pitch and mounting notes.

Table 1: Front Mounted Accessory Screw Hole Sizes

Model	Front Accessory Screw Hole Size / Thread Pitch	Mounting Notes
VLX Wash Luminaire	6-32	<ul style="list-style-type: none"> In all instances, the length of mounting screws depend on thickness of accessory. At least 1/8-inch (3.1750 mm) of the screw needs to go into the assembly. A full 4 turns of the screw head. All mounting screws must be SEMS - integrated lock washer on screw. Accessories should have a secondary safety restraint as per applicable local or national codes.
VLX3 Wash Luminaire	M4 x .7	
VL440 Spot Luminaire	6-32	
VL770 Spot Luminaire	6-32	
VL880 Spot Luminaire	6-32	
VL3500 Wash Luminaire	6-32	
VL3500 Wash FX Luminaire	6-32	
VL4000 BeamWash Luminaire	6-32	



Note: Refer to the current version of Philips Vari-Lite technical notice TN-232 regarding the use of third-party accessories.

CONTACT INFORMATION

If you have any questions as to any aspect of this Technical Notice, please contact Philips Vari-Lite customer service at 1-877-VARILITE or +1-214-647-7880.