### **VARI\*LITE**

### VL1100 ARC ERS



The Vari-Lite VL1100 Arc ERS combines the advantages of an ellipsoidal reflector spotlight with the versatility of an automated luminaire.

Coupled with cool color tones, brightness and intensity, the versatility of the VL1100 Arc ERS is further enhanced with either the mechanical iris or 4-blade shutter system. The VL1100 Arc ERS has a 50kHz drive system that quiets the operation of all two-phase motors in the fixtures during movement and while in static positions. Three-phase, ultra quiet stepper motors provide for smooth, timed continuous pan and tilt motion. Additionally, a central bearing system in the gobo wheel reduces noise and ensures smooth operation.

When the production calls for cool color tones and bright, intense light, designers turn to the VL1100 Arc ERS. The VL1100 Arc ERS luminaire's quiet operation and affordable price make it ideal for budget-conscious productions.



## VL1100 ARC ERS

#### **FEATURES & BENEFITS**

- 575W arc lamp
- More than 15,000 lumens
- · Near silent operation
- Separate ballast can be mounted remotely from fixture
- Arc lamp gives extended life over tungsten version
- Wide zoom range continuously variable field angle in imaging range from 19-36°, super zoom angles to 70°
- · CMY color mixing system
- Rotating gobo wheel 5 + open (gobo sold separately)
- Framing shutter (S version) four blade system can frame and crop beam field and gobos. Each individual shutter is capable of translating to beam centre while also rotating ±35°. Entire shutter rotates ±45°
- Beam size control iris (I version)
- In addition to the zoom optics, a mechanical iris provides continuous beam size control for both rapid changes and smooth timed beam angle changes
- · Convection cooled lamp housing for quite operation
- Two year limited warranty




## VL1100 ARC ERS

SOURCE					
	Source	MSR			
	Lamp cap	G22			
	Wattage	575W			
OPTICAL PERFORMANCE					
	Lumen output (max.)	15,000			
	Color temperature	5900K >90			
	CRI / Ra				
	Dimming system	Mechanical glass wheel / no strobe			
BEAM					
	Beam angle	19-36-70°			
IMAGING					
	Gobo 1	1 x 5 + open rotating interchangeable			
	Prism	No			
	Frost	Variable	Variable		
	Strobe	Mechanical glass wheel / no strobe			
	Framing shutters / beam shaping	Yes (S versions)			
	Iris	Yes (I version)			
MOVEMEN	NT				
	Pan / tilt	540° / 270°			
DATA PRO	OTOCOLS				
	Controls	DMX512-A			
	DMX channels	27			
COLOR					
	Color system	CMY			
POWER					
	Operating voltage	100-240VAC 50/60Hz			
ENVIRON		°C	°F		
	Operating temperature	-29-50°	-20-122°		
PHYSICALS					
	IP rating	IP20			
	Finish	Black	White		
	Construction	Metal frame / engineering plastic covers			

## VARI\*\*LITE

# VL1100 ARC ERS

DIMENSIONS		mm	in		
	HxWxL	445 x 876 x 660	17.5 x 34.5 x 26		
	Hanging centers	635	25		
WEIGHT		kg	Ib		
	Weight	32	70.5		
		7.2 ballast hangs separate	15.9		
WARRANTY & APPROBATION					
	Warranty	2 years			
	Approvals / listings	CE, ETL, UL, FCC CSA, RoHS, ISO 9001			





## VL1100 ARC ERS

VL1100 ARC ERS	VERSION	FINISH	ORDER CODE
Vari-Lite VL1100 Arc ERS	AS	Black	20.9664.0001.12
Vari-Lite VL1100 Arc ERS	AS	White	20.9664.0001.12.02
Vari-Lite VL1100 Arc ERS	Al	Black	20.9664.0001.13
Vari-Lite VL1100 Arc ERS	Al	White	20.9664.0001.13
Luminaire programing kit			PEGASUS

#### © 2018 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 20.9664.0001.12-SpecSheet-01