

# VARI\*LITE

## VL2600 PROFILE



The VL2600 Profile is designed with top-class performance and cost-effective ownership in mind. It produces 19,000 lumens of high color temperature, high contrast light output from its state-of-the-art 550W light engine, with a class-leading zoom range of 7-48°.

It offers a broader choice of saturated colors while maintaining the familiar Vari-Lite color palette from the CMY color system with variable CTO adjustment. Effects features include Iris, two gobo wheels, one fixed color wheel, prism and variable frost. Compact, lightweight, fast and accurate, the VL2600 Profile is engineered to be easy to use, prep and maintain.

A full system lighting solution with dedicated Spot, Wash and Profile fixtures, the VL2600 range combines Vari-Lite quality and performance with the latest LED technology, all engineered to deliver the best possible package to the mid-sized show lighting segment.





# VL2600 PROFILE

## FEATURES AND BENEFITS

- Lower power consumption - approx. 820W (550W LED engine)
- High output - 19,000 lumens
- High color temperature - 7200 CCT
- Good color rendering: - CRI 81 - TM30 Rf/80 Rg/94
- Flat, even beam
- High contrast ratio
- Wide zoom range - 7° to <48°
- Color mixing - CMY + variable CTO
- Beam shaping - Four blade framing system
- Beam reduction - Iris
- Compact design - 464 x 300 x 715mm. Weight 32kg
- Fast and accurate movement (FP=3s, FT=2s)
- Projected Image:
  - 1 Rotating gobo wheel (7 + open, glass gobos)
  - 1 Fixed gobo wheel (8 + open, glass gobos)
- Spilt-beam effects - 1 x 3-facet prism
- Beam diffusion - variable frost

## LIMITED WARRANTY

Every Vari-Lite product is backed by a minimum 2-year limited warranty against manufacturing defects and workmanship. Refer to the Vari-Lite Limited Warranty Card available at [www.vari-lite.com/global/support/warranty](http://www.vari-lite.com/global/support/warranty) for more details.

## VL2600 PROFILE

### SOURCE

<b>Type</b>	LED
<b>Wattage</b>	550W

### OPTICAL PERFORMANCE

<b>Lumen output (max.)</b>	19,000	
<b>Source color temperature</b>	8000K	
<b>Output color temperature</b>	7200K	
<b>CRI / Ra</b>	82	
<b>TM30</b>	Rf/80 Rg/94	
<b>Lux 7° beam @ 5m / 16.41ft</b>	49,075	4,559 Fc
<b>Lux 48° beam @ 5m / 16.41ft</b>	1290	120 Fc
<b>Lux 7° beam @ 10m / 32.8ft</b>	12,300	1143 Fc
<b>Lux 48° beam @ 5m / 32.8ft</b>	326	31 FC
<b>Dimmer / strobe</b>	Electronic 16-bit	

### BEAM

<b>Beam angle</b>	19,000
-------------------	--------

### IMAGING

<b>Gobo wheel 1</b>	Glass interchangeable rotation 7 + open
<b>Gobo wheel 2</b>	Glass interchangeable fixed 8 + open
<b>Prism</b>	3 facet
<b>Frost</b>	Medium
<b>Shutter / framing</b>	4 blades +/-90° rotation
<b>Iris</b>	Yes

### COLOR

<b>Color system</b>	CMY, Variable CTO 1 x fixed color wheels 7 + open
---------------------	--

### MOVEMENT

<b>Pan</b>	540°
<b>Tilt</b>	270°
<b>Pan / Tilt speed</b>	3.4s / 2.5s

### COOLING




<b>Fan</b>	Yes
<b>Studio mode</b>	Yes
<b>Variable speed fan control by DMX</b>	Yes

## VL2600 PROFILE

NOISE LEVELS BASE LEVEL 30DB		
<b>1m / 3.3ft Full operation</b>	48.5 Standard mode full ouput db	
<b>1m / 3.3ft Idle</b>	45.5 Standard mode full ouput db	
<b>Modes</b>	Standard / Studio	
POWER		
<b>Operating voltage</b>	100-240VAC 50/60Hz	
DATA CONNECTIONS		
<b>DMX (RDM)</b>	5-pin XLR In and Thru	
<b>RJ45 data point</b>	In	
DATA PROTOCOLS		
<b>DMX (RDM)</b>	Mode 1 - 46 channels (default mode) Mode 2 - 41 channels	
<b>ArtNET</b>	Yes	
PHYSICALS		
<b>IP rating</b>	IP20	
<b>Finish</b>	Black	
<b>Construction</b>	Metal frame, plastic covers	
ENVIRONMENT		
	<b>°C</b>	<b>°F</b>
<b>Operating temperature</b>	-10-45°	4-113°
DIMENSIONS		
	<b>mm</b>	<b>in</b>
<b>H x W x L</b>	464 x 300 x 715	18 x 12 x28
<b>Hanging centers</b>	500	20
WEIGHT		
	<b>kg</b>	<b>lb</b>
<b>Fixture only</b>	32	70.5
APPROBATIONS		
<b>Approvals / listings</b>	CE, ETL, UL, FCC CSA, RoHS, ISO 9001	



## VL2600 PROFILE





# VL2600 PROFILE


PRODUCT NAME	ORDER CODE
Vari-Lite VL2600 Profile Fixture (Framing) White Body (Includes rails and power input connector)	<b>88-105-7270-10</b>
Vari-Lite VL2600 Profile Black Body (Includes rails and power input connector)	<b>88-105-7340-00</b>
Vari-Lite VL2600 Profile White Body (Includes rails and power input connector)	<b>88-105-7340-10</b>
Luminaire programming kit	<b>PEGASUS</b>

## VL2600 PROFILE

### WHEEL 1


1	Open slot
2	Night sky
3	Circle of ovals
4	Bricked out
5	Punch card
6	Swirl
7	Honeycomb reverse
8	On the rocks*

\*glass gag



### WHEEL 2

1	Open slot
2	Leafy breakup
3	Medium circle
4	Lattice
5	Radial breakup
6	Dust breakup
7	Neurons
8	Grid
9	Cross bars



©2020 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 88-105-7270-00-100-v01