



**PRODUCT:** Various Philips VARI\*LITE Luminaires

**SUBJECT:** Front Lens Accessory Mounting Screw Hole Size Information


### OVERVIEW

This technical notice is for informational purposes only. Users and owners are not required to inspect their Philips VARI\*LITE luminaires. This notice should be kept for future reference.



**Note:** Service and routine maintenance to Philips VARI\*LITE luminaires should be done by an Authorized Service Center or trained and qualified personnel only.

### FRONT LENS ACCESSORY SCREW HOLE SIZES

The following Philips VARI\*LITE luminaires have screw holes on the front of the luminaire head assembly to mount accessories. Refer to [Table 1, “Front Mounted Accessory Screw Hole Sizes,”](#) for screw size/thread pitch and mounting notes.

**Table 1: Front Mounted Accessory Screw Hole Sizes**

Model	Front Accessory Screw Hole Size / Thread Pitch	Mounting Notes
VLX Wash Luminaire	6-32	<ul style="list-style-type: none"> <li>In all instances, the length of mounting screws depend on thickness of accessory.</li> <li>At least 1/8-inch (3.1750 mm) of the screw needs to go into the assembly. A full 4 turns of the screw head.</li> <li>All mounting screws must be SEMS - integrated lock washer on screw.</li> <li>Accessories should have a secondary safety restraint as per applicable local or national codes.</li> </ul>
VLX3 Wash Luminaire	M4 x .7	
VL440 Spot Luminaire	6-32	
VL770 Spot Luminaire	6-32	
VL880 Spot Luminaire	6-32	
VL3500 Wash Luminaire	6-32	
VL3500 Wash FX Luminaire	6-32	
VL4000 BeamWash Luminaire	6-32	



**Note:** Refer to the current version of Philips Vari-Lite technical notice TN-232 regarding the use of third-party accessories.

### CONTACT INFORMATION

If you have any questions as to any aspect of this Technical Notice, please contact Philips Vari-Lite customer service at 1-877-VARILITE or +1-214-647-7880.