

VARI*LITE

VL800 EVENTPAR



The VL800 EVENTPAR is an LED retro-style event PAR perfect for a modern replacement of classic tungsten PAR fixtures. Designed to bring back the vintage stylings of the original lamps and PAR cans but built with the DNA of Vari-Lite, the VL800 EVENTPAR is available in both RGBA and warm white (WW) varieties, with output and color reminiscent of tungsten PAR 64 lamps. With an outdoor rating of IP24 for protection against water spray from any direction, the fixture can withstand rainy conditions at your next outdoor event or installation. To meet the needs of any installation or event, the VL800 EVENTPAR is available in black, white, bronze, or polished aluminum.



VARI*LITE


VL800 EVENTPAR

FEATURES AND BENEFITS

- **Cost-effective LED PAR built by Vari-Lite** - LED PAR from a brand you trust
- **Retro styling, color, and output** - Looks, feels, and functions like a classic tungsten fixture, but with modern capabilities
- **RGBA and WW versions** - Get that perfect tungsten look with output and color that matches the original fixtures
- **Gel color presets matched to traditional gel numbers** - Use the colors you have always used without the need to change gels
- **Outdoor rated (IP24)** - Rated against water spray from any direction, providing weather protection
- **Adjustable frequency to exceed camera frame rates** - Camera -friendly fixtures for IMAG or live televised events
- **Multiple housing finishes available, including black, white, bronze, and polished aluminium** - select the perfect look for any event

LIMITED WARRANTY

Every Vari-Lite product is backed by a minimum 2-year limited warranty against manufacturing defects and workmanship. Refer to the Vari-Lite Limited Warranty Card available at www.vari-lite.com/global/support/warranty for more details.





VL800 EVENTPAR

	RGBA	WARM WHITE		
SOURCE				
Type	LED	LED		
Wattage	1 x 300W RGBA	1 x 200W		
OPTICAL PERFORMANCE				
Output Lumens	3200 lm	10251 lm		
Output CRI	Not applicable	CRI(Ra) >97		
Output CCT	Variable	3000K		
	LUX	FOOT-CANDLES	LUX	FOOT-CANDLES
Narrow @ 5m	4300	399.4	12300	1142.7
Wide @ 5m	295	27.4	940	87.3
Narrow @ 10m	1060	98.5	3400	315.9
Wide @ 10m	90	8.4	300	27.9
BEAM				
Angle	10° - 30°	9° - 30°		
Control	Manual 10°/15°/20°/25°/30°	Manual 10°/15°/20°/25°/30°		
Accessory beam control	Dual rail accessory holder	Dual rail accessory holder		
COLOR SYSTEM				
Color mixing	RGBA (extended blue spectrum control)	Not applicable		
CCT	2700 to 10000K	3000K		
Fixed color	44 calibrated colors	Not applicable		
NOISE LEVELS (BASE LEVEL 18dB)				
Full operation	39dB	39dB		
Standby	25dB	25dB		
Fan modes	Standard, studio, whisper	Standard, studio, whisper		
USER INTERFACE				
Type	Full color invertible screen 4 push button control	Full color invertible screen 4 push button control		
POWER				
Range	100-240 VAC input at 50/60 Hz	100-240 VAC input at 50/60 Hz		
Connector type	Twist-Lock black/yellow - In / Thru	Twist-Lock black/yellow - In / Thru		
Wattage (max)	360W	240W		

VL800 EVENTPAR

DATA CONNECTIONS

DMX (RDM)	In and Thru 5-pin XLR	In and Thru 5-pin XLR	
DMX modes	16-bit	15 channels	5 channels
	8-bit	10 channels	4 channels
		5 channels color mode	1 channel single mode

PHYSICALS

IP rating	IP24*	IP24*
Finish	Black, white, satin light bronze, polished aluminium	Black, white, satin light bronze, polished aluminium

DIMENSIONS (H x W x L)

	mm	in	mm	in
Fixture only	452 x 281 x 418	17.8 x 11.1 x 16.5	452 x 281 x 418	17.8 x 11.1 x 16.5
Packed dimensions	630 x 350 x 390	24.8 x 13.8 x 15.3	630 x 350 x 390	24.8 x 13.8 x 15.3
Hanging type	M12 bolt hole in yoke		M12 bolt hole in yoke	

WEIGHT

	kg	lb		
Fixture only	6.5	14.3	6.5	14.3
Packed weight	Net	6.2	13.7	6.2
	Gross	7.9	17.4	7.9

WARRANTY & APPROBATIONS

Warranty	2 years	2 years
Approval / listings	CE, ETL, UL, FCC CSA, RoHS, ISO 9001	CE, ETL, UL, FCC CSA, RoHS, ISO 9001



* 24= Protection from water spray from any direction



VL800 EVENTPAR

WW OPTIONS	ORDER CODE
VL800 EVENTPAR WW, 1 x 200W 3000K LED PAR 64, manual zoom setting, black powder-coat body w/power connector	912400575001
VL800 EVENTPAR WW, 1 x 200W 3000K LED PAR 64, manual zoom setting white powder-coat body w/power connector	912400576321
VL800 EVENTPAR WW, 1 x 200W 3000K LED PAR 64, manual zoom setting satin light bronze powder-coat body w/power connector	912400576325
VL800 EVENTPAR WW, 1 x 200W 3000K LED PAR 64, manual zoom setting polished aluminium body w/power connector	912400576323
RGBA OPTIONS	ORDER CODE
VL800 EVENTPAR RGBA, 1 x 300W RGBA LED PAR 64, manual zoom setting, black powder-coat body w/power connector	912400575002
VL800 EVENTPAR RGBA, 1x 300W LED PAR 64, manual zoom setting, white powder-coat body w/power connector	912400576322
VL800 EVENTPAR RGBA, 1x 300W LED PAR 64, manual zoom setting, satin light bronze powder-coat body w/power connector	912400576326
VL800 EVENTPAR RGBA, 1x 300W LED PAR 64, manual zoom setting, polished aluminum body w/power connector	912400576324
ACCESSORIES	ORDER CODE
VL800 EVENTPAR Barndoor finished in Black	912400576366
VL800 EVENTPAR Barndoor finished in White	912400576367
VL800 EVENTPAR Barndoor finished in Polished Aluminum	912400576368
VL800 EVENTPAR Barndoor finished in satin light bronze	912400576369

©2021 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 912400575001-100-A